

Press "volume +" and "volume -" to adjust the image definition.

Slip "fn" key on the bottom of remote-control to the left side

when image definite, focusing function is turned off.


focusing function is turned on.



Remote-control pairing


Note: Please charge the remote-control for 30 minutes before

- Please put the remote-control within 10 cm from the device.
- Press "return" and "home" at the same time, green indicator light blinks for 3 seconds, blue indicator light quickly blinks. Then release the buttons, remote control is pairing. If pairing is successful, blue indicator light flashes continuously for 2 seconds and then extinguishes. If pairing is failed, exit pairing mode after 30-seconds timeout, follow the steps above to pair



3. Charge the remote-control

 When the red indicator appears and blinks, please charge the remote-control.



4. Introduction of remote-control functions

- Slip "fn" key on the bottom of remote-control to the right side, focusing function is turned on. Press "volume +" and "volume -" to adjust the image definition.
- Slip "fn" key on the bottom of remote-control to the right side. gravity sensor function is turned on. Pairing with games that support gravity sensor and use remote-control horizontally. gravity sensor function is turned off. When gravity sensor indicator light flashes continuously
- Quickly and forcibly shake the remote-control to turn on/off the mouse function.
- Menu key function Short press "menu key (≡)" to open menu function, long press
- "menu key (\equiv)" to open shortcut function. Power status Red indicator light flashes continuously when remote-control is charging; green indicator light flashes continuously when charging is completed; red indicator light quickly blinks for 4

times when power is low; red indicator light quickly blinks for

10 times when power is very low, remote control has to be

- Stand-by and sleep conditions Under working mode, remote-control will enter sleep condition when it is standing for more than 10 seconds, it can be awoken
- by pressing any button. If remote-control's system is crashed, press reset button, then
- release reset button, red indicator light will blink for 3 times, reset

5 Switch Desktop Versions

 Press "up" key of remote control on home page to access shortcut entry, then switchover between standard version and business version.

- System setup>General setup>Desktop version, switchover between standard version and business version.
- 6 Switch languages
 - System setup >international setting, to choose your language and time zone.

7 Application management

- Aptoide App market >Press search symbol > enter the application name and download. Use mouse function if any APP does not work with remote.
- Aptoide> updates, to update your installed application.
- Application move/delete Choose the App you want to change, long press "OK" key to move/ uninstall/ collect it.

8 Projection setup

- Keystone correction System setup>projection setup, press "OK" key to choose adjust point. After choosing a point, use "direction" keys to adjust keystone horizontally or vertically. After completing the adjustment, press "return" key to save adjustment and return
- Projection mode setup System setup > projection setup > projection mode setup, choose projection mode according to device placed condition.
- frame size and aspect ratio.
- Long press "menu (\equiv) " key for 2 seconds, release "menu" key, shortcut setting function will popup on the bottom of

screen, adjust the image according to your preference.

Chengdu XGIMI Technology Co.,Ltd.

System setup > general > keyboard, choose input method.

- System setup > about > device name, to choose or customize
- 9 System update

Online update

 System setup > About > System update, device will send update notification when system detected current version is not the latest version, press "online update" to update

2. USB update

- Go to XGIMI official website to download USB force update patch, decompress the file and send to USB.
- Connect the device to power supply, then plug USB in USB 2.0 port of the device.
- System setup > about > system update > USB update, wait for force update complete.
- Or insert RESET hole with a needle, and then open the lens
- Wait until the system enters update interface, loosen the
- button and wait for update complete. Note: please do not remove USB or power supply during
- updating process, please use FAT32 form USB.

10 Video playing setup

subtitle menu to set subtitle.

- Play progress adjustment Use "left" and "right" keys to adjust play progress.
- Subtitle setup

When playing a video, press "menu (≡) " key to choose

- When playing a video, press "menu (\equiv) " key to choose 3D setup menu and set 3D mode.
- 11 Device connection & mirroring display
- System setup > network setup > WiFi setup, choose a network and connect with it.
- System setup > network setup > WiFi hotspot, turn on WiFi hotspot to let other devices find this WiFi hotspot in their WiFi setting, enter password of this hotspot and connect to XGIMI
- System setup > network setup > Miracast, turn on Miracast, mobile phone or PC that support Miracast can connect XGIMI
- System setup > network setup > AirPlay, turn on AirPlay, mobile phone or PC that support AirPlay can connect XGIMI and use it as mirroring display.
- System setup > Bluetooth & external device, pair and connect with external blue tooth devices, e.g. speaker,
- Wired setup System setup > network setup > wired setup, plug internet cable into the internet port which is at the back of XGIMI.
- 12 Resource management

remote-control, and gamepad.

Add device

FileManager > add device, choose the device and add remote

2. File management

• FileManager>long press "OK" key, selection box appears. Press "menu (≡) " key to choose copy/ cut/ paste/ delate/

File viewing

 Plug in USB, press "File Manager", view the files of USB device, press "menu (\equiv) " key to open more functions.

4. Magic popup

- Stay on home page, press "up" key to open shortcut entry of desktop versions/ WiFi setup/ Bluetooth/ eject USB.
- Stay on home page, press "down" key to open collection entry at the bottom of screen, users are able to add favorite Apps in collection entry and quickly open the Apps.
- Stay on home page, press "left" key until the end to open input shortcut entry at the left side of screen, and choose

5. Cleaning memory

- When App's operation breaks down, use "Clear memory" App to clean the backstage, then enter again.
- 13 XGIMI Assistance
 - Scan the QR code to download XGIMI assistant

· mobile phone remote: device can be easily controlled by mobile

- mobile phone resource: send the resource from mobile phone
- mirroring display control: mirroring to mobile phone, support gravity sensor games.



Product specification

Display technique

Optical parameters	Lens	High light transmission
		coated lens
	Specialty	3D
	Luminance	700ANSI lumen
	Luminance uniformity	98%
	Colorgamut	>=120%NTSC
	Contrast	5000:1
	Standard resolution	WXGA(1280x800)
	Compatible resolution	1080P/ 2K/ 4K
Projection parameters	Projection ratio	1.2:1(76-inch@2M)
	Keystone correction	Vertical: ± 35 degree,
		horizontal: ±30 degree
	Projection method	Forward/ backward/
		hang ceiling
System parameters	CPU	4 core 1.5GHz
	GPU	Mali-450MP4
	RAM	2GB DDR3
	Storage	16GB eMMC
	System	Android4.3
	Mirroring display	Airplay/ DLNA/Miracast
Ports		HDMIx2
		USB2.0x1
		USB3.0x1
		AVx1
	Outputport	Headphone/SPDIFx1
	Cable network	Ethernetx1
	WiFi	Dual-band 2.4/5GHz,
		802.11a/b/g/n/ac2x2
		double antennas
	Bluetooth	Bluetooth 4.0/ BLE

0.45"DMDRGB-LED 48-90W

Size	196x196x50mm
Weight	1.2kg
Power plug	x1
Power cable	x1
Bluetooth remote-control	x1
Remote-control charge cable	x1
Handbook	x1
Adapter	x1
Retaining screw	x4
	Weight Power plug Power cable Bluetooth remote-control Remote-control charge cable Handbook Adapter



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference.

2. This device must accept any interference received, including interference that may cause undesired operation.



XGIMI™